



Emergency Rescue Hardware by BEST



Trusted experts. Proven reliability. Simply BEST.


Emergency Rescue Hardware

For a variety of door applications including patient rooms in hospitals, institutions, and convalescent homes to private baths. Permits doors to normally swing into the bath, thus saving space, yet swing out into the bedroom, in case of emergency when a patient is trapped inside. Stanley hospital rescue hardware is composed of a Stanley DAP-3 (Double acting pivot), ES-1 (Emergency Door Stop), and DLS-1 or DSL-2 (Double Lipped Strike).

Double Acting Pivot

DAP-3 – (ANSI A2742) – Brass and malleable iron – standard finishes

- Heavy duty pivot assembly for commercial double acting interior doors of average frequency use, weighing up to 135 lbs. (61 Kg) and not exceeding 3' (91 mm) in width
- For 1-3/8" (35 mm) and 1-3/4" (44 mm) thick doors
- Header plate has a walking beam design to simplify door installation
- Extra heavy 1/4" (6.35 mm) thick solid brass frame plates
- Oil impregnated bronze bearing in top door plate
- Smooth acting ball bearing assembly in bottom door plate
- For door undercuts in 1/16" (1.6 mm) increments from 3/4" (19 mm) to 1" (25 mm)
- Bottom bracket is frame mounted and must be floor supported
- The recommended positioning of the door is to inset it 1/8" (3.2 mm) from the bathroom face of the frame



65KL5 Deadlocking Latch Specifications


Pivot point 1-1/4" (31.8 mm) from jamb

Header plate (brass) – 4-7/8" x 7/8" x 1/4" (124 mm x 22 mm x 6.4 mm)

Top door plate (malleable iron) – 4-3/8" x 1" x 1/4" (111 mm x 25.4 mm x 6.4 mm)

Bottom jamb bracket (brass) – 3" x 1-1/4" x 1/4" (76 mm x 32 mm x 6.4 mm)

Bottom door plate (malleable iron) – 4-3/8" x 1" x 1/4" (111 mm x 25.4 mm x 6.4 mm)



Flat Head Screws Per Piece	Sets Per Box	Sets Per Case	Weight	
			Lbs.	(Kg)
4-14 x 1 1/2 wood screws	1	20	37	(17)
5-1/4-20 x 1/2 machine screws				

Emergency Rescue Hardware

Emergency Door Stop

ES-1 – (ANSI A1882) – Extruded and cast brass – standard finishes

- For converting double acting doors to single acting doors
- Emergency release allows door to swing open in opposite direction to reach ill patients who fall and block normal path of door
- Stop release resets automatically. Spring action stop, with finger-tip release, using pullman-type latch bolt with rubber bumper insert
- Refer to template for door clearance




ES-1

65KL5 Deadlocking Latch Specifications

Surface plate – 4-1/2" x 1-5/8" (114 mm x 41 mm) bolt height 2" (51 mm)

Case – 2-1/8" x 1-5/16" (54 mm x 33 mm)


Flat Head Screws Per Piece	Pieces Per Box	Pieces Per Case	Weight	
			Lbs.	(Kg)
4-12-24 x 1/2 brass machine screws	1	30	17	[8]



Holdback for ES-1

HB-1 – Steel – standard finishes

- Used with ES-1 to allow doors to become double acting by holding emergency stop in depressed position
- Attaches to surface plate of ES-1
- Packed one in envelope with mounting instructions



Double Lipped Strikes

DLS-1 – For 1/8" (3.2 mm) Inset hung doors – Brass – standard finishes

DLS-2 – For center hung doors – Brass – standard finishes

- Allows center hung doors to be opened in both directions without damage to frame
- Available for 5-3/4" (146 mm) cased openings
- Latch bolt cut out is 1-1/4" x 11/16" (32 mm x 17.5 mm) ANSI standard for Heavy
- Duty bored type locks.
- For mortise locks consult factory.
- .093" (2.4 mm) material

DLS- & DLS-2

Flat Head Screws Per Piece	Pieces Per Box	Pieces Per Case	Weight	
			Lbs.	(Kg)
8-32 x 1/2 brass machine screws	1	50	30	[13.6]



DLS-1

DLS-2



CORPORATE HEADQUARTERS

6161 EAST 75TH STREET
INDIANAPOLIS, IN 46250 USA

Phone 855-365-2407

bestaccess.com

For questions about ordering and to be sure you get the right configuration for your needs, [contact your BEST dormakaba sales representative.](#)
6161 East 75th Street, Indianapolis, IN 46250 USA | [855-365-2407](tel:855-365-2407) | bestaccess.com

BEST is a trademark of dormakaba Holding® 2021 All rights reserved. BEST is a member of the dormakaba Group, one of the top three providers for access and security solutions, globally.

dormakaba 

SAH014 12/21